



# TWO POST LIFTS TO MEET YOUR EVERY NEED.

**BP9**



Capacity:	9,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	138 1/2"
Overall height:	114 1/4"
Ceiling requirement:	113"
Front and Rear Arms:	2-stage symmetric

**F10**



Capacity:	10,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	131" or 137"
Overall height:	143"
Ceiling requirement:	144"
Front and Rear Arms:	3-stage / 2-stage

**i10**



Capacity:	10,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	131" or 137"
Overall height:	143"
Ceiling requirement:	144"
Front Arms:	Spot Rite™ 3-stage

**DP10A**



Capacity:	10,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	131" or 137"
Overall height:	143"
Ceiling requirement:	144"
Front Arms:	Spot Rite™ 3-stage

**F12**



Capacity:	12,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	140" or 146"
Overall height:	143" to 166"
Ceiling requirement:	144" to 168"
Front and Rear Arms:	2-stage

**i12PRO**



Capacity:	12,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	140" or 146"
Overall height:	143" to 166"
Ceiling requirement:	144" to 168"
Front and Rear Arms:	3-stage

**DP15**



Capacity:	15,000 LBS
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	154 3/8"
Overall height:	154 3/4" to 199"
Ceiling requirement:	155 3/4" to 201"
Front and Rear Arms:	2-stage

**DP18**



Capacity:	18,000 lbs
Vehicle class:	1 2 3 4 5
Column:	symmetric
Overall width:	154 3/8"
Overall height:	154 3/4" to 199"
Ceiling requirement:	155 3/4" to 201"
Front and Rear Arms:	2-stage

**Two-post features.**

**Spot-Rite™ 3-Stage Front Arms** accommodate vehicles both symmetrically and asymmetrically. This feature allows the technician to position the vehicle doors in front of or behind lift columns to prevent door damage.

**Color options.** Keep the look of your equipment clean and cohesive with two post blue and red color options.



Learn more about our two post lineup at [forwardlift.com](http://forwardlift.com).